

HANWHA 8600L

Low Density Polyethylene

Hanwha Chemical

Message:

CLNA-8600L is a low density polyethylene(LDPE) compound designed for the insulation of coaxial cable and radio frequency communication cables. It has excellent electrical properties. CLNA-8600L is commonly used by blending with CHNA-8600H prior to extrusion. Recommended blend ratios of 8600H/8600L/Nucleating agent are 68~78 / 30~20 / 2 %.

Applications:

8600H&L can be used coaxial cable and radio frequency(RF) communication cables using a gas injection foaming process.

General Information			
Features	Foamable		
	Good Electrical Properties		
	Low Density		
Uses	Blending		
	Communication Wire Insulation		
	Wire & Cable Applications		
Agency Ratings	ASTM D 1248, I, Class A, Cat. 3		
Forms	Pellets		
Processing Method	Extrusion		
	Foam Processing		
	Gas-Assisted Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.921	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	2.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	11.8	MPa	ASTM D638
Tensile Elongation (Break)	600	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	< -76.0	°C	ASTM D746
Electrical	Nominal Value	Unit	Test Method
Volume Resistivity	> 1.0E+16	ohms · cm	ASTM D257
Dielectric Constant (1 MHz)	2.28		ASTM D150
Dissipation Factor (1 MHz)	8.0E-5		ASTM D150
Extrusion	Nominal Value	Unit	
Melt Temperature	160 to 200	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any

infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

