

Asaprene™ T-439

Styrene Butadiene Styrene Block Copolymer
AKelastomers

Message:

Asaprene™ T-439 is a Styrene Butadiene Styrene Block Copolymer (SBS) material. It is available in Asia Pacific or Europe. Primary attribute of Asaprene™ T-439: High Flow.
Typical application of Asaprene™ T-439: Adhesives/Tapes

General Information			
Features	High Flow		
Uses	Adhesives		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.950	g/cm ³	ISO 1183
Styrene/Butadiene	45/55	%	Internal Method
Viscosity			Internal Method
15% solution in toluene	25	mPa · s	
25% solution in toluene	170	mPa · s	
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore A, 23°C, 2.00 mm, Compression Molded)	83		ISO 7619
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress ¹ (300% Strain, 23°C, 2.00 mm)	4.00	MPa	ISO 37
Tensile Stress ² (Break, 23°C, 2.00 mm)	6.00	MPa	ISO 37
Tensile Elongation ³ (Break, 23°C, 2.00 mm)	880	%	ISO 37
NOTE			
1.	Type 1A		
2.	Type 1A		
3.	Type 1A		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT