

# Fixmaster Twin-Weld Adhesive

Epoxy; Epoxide

Loctite®

## Message:

Fixmaster Twin-Weld Adhesive is an Epoxy; Epoxide (Epoxy) product filled with glass fiber. It is available in North America. Applications of Fixmaster Twin-Weld Adhesive include adhesives/tapes and repairing material. Primary characteristic: good adhesion.

General Information			
Filler / Reinforcement	Glass Fiber		
Features	Good Adhesion		
Uses	Adhesives		
	Bonding		
	Repairing Material		
Forms	Pellets		
Hardness	Nominal Value	Test Method	
Durometer Hardness (Shore D)	85	ASTM D2240	
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	41.4	MPa	ASTM D638
Compressive Strength	75.8	MPa	ASTM D695
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	82.2	°C	ASTM D794
Thermoset	Nominal Value	Unit	
Pot Life (25°C)	15 to 20	min	
Demold Time (25°C)	180	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

