## Escorene™ Ultra UL 00114

Ethylene Vinyl Acetate Copolymer Resin

ExxonMobil Chemical

## Message:

UL00114 is a fractional MI copolymer of ethylene and vinyl acetate.

General Information			
Physical	Nominal Value	Unit	Test Method
Vinyl Acetate Content	14.0	wt%	ExxonMobil Method
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus <sup>1</sup>	67.5	МРа	ASTM D638
Tensile Elongation <sup>2</sup> (Break)	> 100	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	70.7	°C	ASTM D1525

本产品不宜在与食品接触的应用中使用.未经埃克森美孚化工书面允许,该产品包括其产品名称,不得在任何医疗应用领域 予以使用或者测试.有关详细的产品监管信息,请联系客户服务.

NOTE	
1.	5.0 mm/min
2.	500 mm/min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

