

# Koylene SS30NS

Polypropylene Homopolymer

Reliance Industries Limited

## Message:

Koylene SS30NS is a Polypropylene Homopolymer (PP Homopolymer) product. It can be processed by extrusion and is available in Asia Pacific. Typical application: Film. Primary characteristic: homopolymer.

General Information			
Features	Homopolymer		
Uses	Bi-axially Oriented Film		
Forms	Granules		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.905	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	3.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	32.4	MPa	ASTM D638
Tensile Elongation (Yield)	12	%	ASTM D638
Flexural Modulus	1320	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	44	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	152	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT