Ravaflex EPM

Ethylene Propylene Copolymer

Ravago Group

Message:

Reprocessed copolymer of ethylene and propylene with a very good processibility.

General Information	
Features	Copolymer
	Antioxidation
	Workability, good
Appearance	White
	Grey

Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.860	g/cm³	ASTM D297
Mooney Viscosity (ML 1+4, 125°C)	20 - 35	MU	ASTM D1646
Ethylene Content	55.0 - 70.0	wt%	ASTM D3900
Antioxidant Additive	None		
Moisture Content (105°C)		%	Internal method
Ash content-1 hr (550°C)		%	ASTM D297
	1000		

Packaging	510000	g
Additional Information	Nominal Value	Unit

It shows an excellent resistance to oxidative and ozone degradation. It is used in bitumen and in plastics modification.

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

