

Nipolon® Hard 5600

High Density Polyethylene

TOSOH Corporation

Message:

Nipolon®Hard 5600 is a high density polyethylene material. This product is available in North America, Europe or Asia Pacific region. The processing methods are: blow molding film, blow molding, extrusion or injection molding.

Nipolon®The main features of Hard 5600 are:

high strength

high hardness

Good processability

Typical application areas include:

container

bag/lining

packing

Jars

home apps

General Information	
Features	High tensile strength
	Workability, good
	High hardness
Uses	Bags
	Industrial container
	Drum
	Household goods
	Bottle
	Food packaging
	Toys
	Web
	Fuel Tank
	Loading box
Forms	Particle
Processing Method	Blow film
	Blow molding
	Extrusion
	Injection molding

Thermal	Nominal Value	Unit	Test Method
Melting Temperature	135	°C	DSC

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT