

Catalyst CT/2-HP UV

Polyolefin
Solvay Specialty Polymers

Message:

Catalyst CT/2-HP is a polyolefin masterbatch, which is used as cable silane crosslinkable mixture according to the recommended dosage. specially designed for Cogegum® And Polidiemme® Series of compounds were developed to improve the properties of elastomers. Catalyst CT/2 can be widely used due to its catalytic activity and anti-aging effect on the final product. Contains metal passivator and can directly contact untinned copper.

General Information			
Features	Light stabilization		
	Copper contact stability		
	Halogen-free		
Uses	Wire and cable applications		
RoHS Compliance	RoHS compliance		
Appearance	Natural color		
Physical	Nominal Value	Unit	Test Method
Specific Gravity ¹	0.900	g/cm ³	ASTM D792
Apparent Density ²	0.50	g/cm ³	ISO 60
Additional Information			
存储产品必须按下列条件存储:-密封,包装袋完好 环境温度不超过35℃ -避免在阳光下曝晒和露天放置 存放时间过长会造成产品性状改变. 保质期:12个月 如果没有满足上述条件,苏威特种聚合物不承担任何责任. 存放时间过长会造成产品性状改变.苏威特种聚合物建议按照包装印制生产日期,在12个月内使用完毕.如果没有满足上述条件,苏威特种聚合物不承担任何责任.包装-采用防潮袋包装,每袋25kg,或1375kg堆放于货板供应.-1000kg纸箱包装			
NOTE			
1.	Test on the press plate		
2.	Particle test		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT