

PolyFlo PFA PF-340

Perfluoroalkoxy

PolyFlo, Inc.

Message:

PolyFlo PFA PF-340 is a Perfluoroalkoxy (PFA) material. It is available in North America.

General Information		
Physical	Nominal Value	Unit
Specific Gravity	2.12 to 2.17	g/cm ³
Melt Mass-Flow Rate (MFR)	10 to 15	g/10 min
Hardness	Nominal Value	Unit
Durometer Hardness (Shore D)	55 to 57	
Mechanical	Nominal Value	Unit
Tensile Strength (23°C)	24.8 to 33.1	MPa
Tensile Elongation (Break, 23°C)	> 300	%
Thermal	Nominal Value	Unit
Melting Temperature	300 to 315	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

