

Magnobond 6663-1

Epoxy; Epoxide

Magnolia Plastics, Inc.

Message:

Magnobond 6663-1 is an Epoxy; Epoxide (Epoxy) product. It can be processed by potting and is available in North America.

General Information			
Forms	Liquid		
Processing Method	Potting		
Mechanical	Nominal Value	Unit	Test Method
Compressive Strength	103	MPa	ASTM D695
Thermoset	Nominal Value	Unit	Test Method
Thermoset Components			
Hardener	Mix Ratio by Weight: 15		
Resin	Mix Ratio by Weight: 100		
Pot Life (25°C)	40	min	
Shelf Life (25°C)	26	wk	
Thermoset Mix Viscosity	45000	cP	ASTM D2393
Demold Time (24°C)	1400 to 2900	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

