

# Witcom PS 2011/267

General Purpose Polystyrene  
Witcom Engineering Plastics B.V.

Message:

Witcom PS 2011/267 is a General Purpose Polystyrene product. It is available in Europe.  
Characteristics include:  
Flame Rated  
Lubricated

General Information			
Additive	Lubricant		
Features	Lubricated		
Physical	Nominal Value	Unit	Test Method
Density	1.06	g/cm <sup>3</sup>	ISO 1183
Molding Shrinkage - Flow (3.00 mm)	0.40 to 0.70	%	ISO 2577
Water Absorption			ISO 62
Saturation, 23°C	0.10	%	
Equilibrium, 23°C, 50% RH	0.10	%	
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	< 30.0	MPa	ISO 527-2
Tensile Strain (Break)	> 40	%	ISO 527-2
Flexural Modulus	2600	MPa	ISO 178
Flexural Stress	42.0	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength	6.0	kJ/m <sup>2</sup>	ISO 180/1A
Unnotched Izod Impact Strength	35	kJ/m <sup>2</sup>	ISO 180/1U
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (1.8 MPa, Unannealed)	80.0	°C	ISO 75-2/A
CLTE - Flow	8.0E-5	cm/cm/°C	ISO 11359-2
RTI Imp (3.00 mm)	60.0	°C	UL 746
Flammability	Nominal Value		Test Method
Flame Rating (3.00 mm)	HB		ISO 1210

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

