

Dylite® F271TL

Expanded Polystyrene

NOVA Chemicals

Message:

Dylite® F271TL is an Expanded Polystyrene material. It is available in North America for foam processing.

Important attributes of Dylite® F271TL are:

- Low to No Odor/Taste
- Fast Molding Cycle
- Food Contact Acceptable
- Good Aesthetics
- High Gloss

Typical applications include:

- Food Contact Applications
- Containers
- Kitchenware

General Information			
Features	Fast Molding Cycle		
	Food Contact Acceptable		
	Good Surface Finish		
	High Gloss		
	Low to No Odor		
	Low to No Taste		
	Thermally Insulating		
Uses	Containers		
	Cups		
Agency Ratings	EU 2002/72/EC		
	FDA 21 CFR 177.1640		
	FDA 21 CFR 178.3010		
Processing Method	Foam Processing		
Physical	Nominal Value	Unit	
Apparent Density	0.61 to 0.64	g/cm ³	
Pentane Content	5.3 to 5.9	wt%	
Bead Size - T - Fine	300.0 to 500.0	µm	
Thermal Resistance - R-value	4.20	1/in	
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	80.0	°C	
CLTE - Flow	6.3E-5	cm/cm/°C	ASTM D696
Thermal Conductivity	0.034	W/m/K	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

