

Varcum 29008

Phenolic

Durez Corporation

Message:

Varcum 29008 is a non-heat reactive, alkyl-substituted, solid phenolic resin supplied in flake form.
Tackifier for chlorobutyl rubber in white sidewall and tire inner liner compounds.
Tackifier for SBR, butyl and other synthetic rubbers.
Recommended for the production of high grade oleo resinous varnishes.
Can be used directly, or for blending with alkyd resins.
Varnishes formulated utilizing this resin may be used as vehicles in pigmented enamels.
Not recommended for white or very light colored enamels.
Contains no modifying agents and is suitable for use with any of the typical drying oils used in varnish formulations
Good gas proofing characteristics.
Varnishes exhibit excellent drying characteristics and dried films have exceptional resistance to alkalies and water.
For optimum control, varnish cooks of the dispersion type are recommended.

General Information			
Uses	Adhesives		
	Blending		
Forms	Flakes		
Physical	Nominal Value	Test Method	
Color	< 6.0	Internal Method	
Softening Point - B&R;	130	°C	Internal Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT