

Toraypef® 15020 AP5M

Polyolefin

Toray Resin Company

Message:

Toraypef® 15020 AP5M is a Polyolefin product. It can be processed by foam processing or injection molding and is available in Asia Pacific, Europe, or North America. Typical application: Foam. Primary characteristic: heat resistant.

General Information	
Features	High Heat Resistance
Uses	Foam
Forms	Pellets
Processing Method	Foam Processing Injection Molding

Physical	Nominal Value	Unit
Specific Gravity ¹	0.0670	g/cm ³
Shrinkage ²		
MD : 120°C	-2.1	%
TD : 120°C	-1.7	%
Thickness	2.00	mm
Compressive Hardness - 25%	0.155	MPa
Elongation		
MD	240	%
TD	220	%
Gel Fraction	52	%
Thermoforming Ratio - H/D	0.570	

Elastomers	Nominal Value	Unit
Tensile Strength		
Across Flow : Yield	1.43	MPa
Flow : Yield	1.77	MPa
Tear Strength		
Across Flow	8.90	kN/m
Flow	7.80	kN/m

NOTE	
1.	Foamed
2.	60 min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

