

# HANWHA P-2500

Polyvinyl Chloride

Hanwha Chemical

## Message:

Feature: High thermal-resistance, weather-proof, cold resistance and mechanical strength. It can have rubber elasticity by adding large amount of plasticizer

Use: Special heat-resistant electric cable covering, flexible hose and leather

General Information			
Features	Good Strength		
	Good Thermal Shock Resistance		
	Good Thermal Stability		
	Good Weather Resistance		
	High Heat Resistance		
Uses	Cable Jacketing		
	Hose		
	Synthetic Leather		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.38 to 0.52	g/cm <sup>3</sup>	ASTM D1895
Particle Size - 42Mesh(350µm) Sieve Pass %	100	%	Internal Method
Volatile Matter	< 0.30	%	ASTM D3030
Degree of Polymerization			
DP	2300 to 2700		JIS K6720-2
K-Value	83.0		DIN 53726

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT