

SolVin 271DF

Polyvinyl Chloride
INOVYN

Message:

Polyvinyl chloride made by suspension polymerisation.
APPLICATIONS:
Cable sheathing and insulation, flexible films and sheets, waterproof membranes, flexible profiles.

General Information			
Uses	Cable Jacketing		
	Film		
	Flexible Cord Insulation		
	Membranes		
	Profiles		
	Sheet		
Processing Method	Calendering		
	Extrusion		
	Extrusion Blow Molding		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.50	g/cm ³	ISO 60
K-Value	71.0		ISO 1628-2
Sieve Analysis			ISO 1624
Retained on 0.063 mm sieve	> 95	%	
Retained on 0.250 mm sieve	< 1.0	%	
Volatile Matter	< 0.30	%	ISO 1269
Residual Vinyl Chloride Monomer	< 1	ppm	ISO 24538

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT