

K-Prene XL-A40

Polypropylene + EPDM Rubber

Technovinyl Polymers India Ltd.

Message:

K-Prene XL-A40 is a Polypropylene + EPDM Rubber (PP+EPDM) material. It is available in Africa & Middle East.

General Information			
Appearance	Natural Color		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.990	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	40		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Set ¹ (23°C)	10	%	ASTM D412
Tensile Stress			ASTM D412
100% Strain	1.00	MPa	
300% Strain	1.50	MPa	
Tensile Strength (Yield)	3.20	MPa	ASTM D412
Tensile Elongation (Break)	600	%	ASTM D412
Tear Strength	15.0	kN/m	ASTM D624
Compression Set			ASTM D395
70°C, 22 hr	35	%	
100°C, 22 hr	45	%	
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	< -60.0	°C	ASTM D746
Additional Information	Nominal Value		
Ozone Resistance - 70 hrs	Pass		
NOTE			
1.	10 min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT