

PANDEX TP-1318

Polyurethane
DIC Corporation

Message:

PANDEX, WALL-LITE series are single-pack and twin-pack polyurethane resins developed for waterproofing of rooftops and walls and adhesion of rubber chips. The series characteristically excel in workability and hardening effects.

General Information		
Features	Good Processability	
	Low to No Water Absorption	
Uses	Adhesives	
	Sealants	
Appearance	Grey	
	Yellow	
Forms	Liquid	
Hardness	Nominal Value	Test Method
Durometer Hardness (Shore A)	55	JIS A6021
Elastomers	Nominal Value	Unit
Tensile Strength (Yield)	3.20	MPa
Tensile Elongation (Break)	600	%
Tear Strength	16.0	kN/m
Fill Analysis	Nominal Value	Unit
Melt Viscosity		
25.0°C ¹	15.0	Pa · s
25.0°C ²	8.00	Pa · s
Additional Information	Nominal Value	Unit
Mixing Ratio	1 : 2	
NOTE		
1.	Hardening Agent	
2.	Base Resin	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

