

Yanshan PE 6380M

High Density Polyethylene
SINOPEC Beijing Yanshan Petrochemical

Message:
Yanshan PE 6380M is a High Density Polyethylene product. It can be processed by extrusion and is available in Asia Pacific. Typical application: Plumbing/Piping/Potable Water.

General Information			
Uses	Piping		
Agency Ratings	PPI PE-80		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.950	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR)	0.10	g/10 min	ASTM D1238
Environmental Stress-Cracking Resistance	1500	hr	ASTM D1693
Ash Content	0.010	%	
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	22.0	MPa	ASTM D638
Tensile Elongation (Break)	600	%	ASTM D638

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT