

KEP® 370F

Ethylene Propylene Diene Terpolymer

Kumho Polychem Co., Ltd.

Message:

Features:

High mooney viscosity & excellent processability very high ENB content & ultra fast vulcanization speed, suitable for blending with diene Rubbers

Applications:

Weather strip body/door seal, gasket, packings, general sponges etc.

General Information		
Features	Good Processability	
	High Viscosity	
	Vulcanizable	
Uses	Automotive Applications	
	Blending	
	Gaskets	
	Seals	
	Windows & Doors	
Forms	Bale	
Physical	Nominal Value	Unit
Mooney Viscosity (ML 1+4, 125°C)	69	MU
Ethylene Content	59.0	wt%
Ethylidene Norbornene (ENB) Content	8.1	wt%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

