

Alathon® H6018

High Density (MMW) Polyethylene
LyondellBasell Industries

Message:

ALATHON H6018 is a medium molecular weight high density homopolymer. Typical applications include cast film for food overwrap and blending with LDPE to formulate medium to high density blends for extrusion coating and extrusion lamination.

General Information	
Features	Food Contact Acceptable Homopolymer
Uses	Blending Cast Film Coating Applications Film Laminates
Agency Ratings	FDA 21 CFR 177.1520
Forms	Pellets
Processing Method	Extrusion Coating Film Extrusion

Physical	Nominal Value	Unit	Test Method
Density	0.960	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	18	g/10 min	ASTM D1238
Extrusion	Nominal Value	Unit	
Melt Temperature	199	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT