

Huaxia Shenzhou DS605

Fluoropolymer

Shandong Huaxia Shenzhou New Material Co., Ltd.

Message:

Fluorinated ethylene-propylene powder, as a copolymer of tetrafluoroethylene and hexafluoropropylene, has good heat stability, outstanding chemical inertness, excellent electrical insulation and low friction coefficient, and can be processed by a thermoplastic processing method. It can mix with telfon powder.
Execution standard: Q/DYS 003-2007

General Information		
Features	Copolymer	
	Electrically Insulating	
	Good Chemical Resistance	
	Good Thermal Stability	
	Low Friction	
Uses	Liners	
Appearance	White	
Forms	Powder	
Physical	Nominal Value	Unit
Melt Mass-Flow Rate (MFR)	< 0.80	g/10 min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT