

Caltex PP MT42FC

Polypropylene

GS Caltex

Message:

Caltex PP MT42FC is a Polypropylene material. It is available in Asia Pacific.

General Information			
UL YellowCard	E319107-100074943		
Features	Paintable		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.00	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	7.0	g/10 min	ASTM D1238
Molding Shrinkage			ASTM D955
Flow	1.2	%	
Across Flow	1.1	%	
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	68		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	21.1	MPa	ASTM D638
Tensile Elongation (Break)	430	%	ASTM D638
Flexural Modulus	1910	MPa	ASTM D790A
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ASTM D256
--	450	J/m	
-10°C	69	J/m	
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	127	°C	ASTM D648
Additional Information	Nominal Value	Unit	
Processing Temperature	210 to 230	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

