Spartech Polycom SC2F-1090

High Impact Polystyrene

Spartech Polycom

Message:

Spartech SC2F-1090 is a medium viscosity, flame retardant, high impact polystyrene (HIPS) resin for injection molding. It is heat stabilized and lubricated for good processing characteristics.

HIPS are rubber modified styrenics that typically contain 1-10% rubber by weight. They offer dimensional and physical stability in moist environments and provide good chemical resistance. These materials also exhibit good flexibility along with good toughness.

A very versatile product for a wide variety of applications, Spartech SC2F-1090 is recommended for industrial, transportation, sporting goods and electrical/electronic applications.

General Information					
Additive	heat stabilizer Lubricant				
	Flame retardancy				
Features	Good dimensional stability				
	Impact resistance, good				
	Workability, good				
	Good flexibility				
	Good chemical resistance				
	Thermal Stability				
	Thermal stability, good				
	Good toughness				
	Lubrication				
	Medium viscosity				
	Flame retardancy				
Uses	Electrical/Electronic Applications				
	Industrial application				
	Application in Automobile Field				
	Sporting goods				
Appearance	Available colors				
	Natural color				
Forms	Particle				
Processing Method	Injection molding				
Physical	Nominal Value	Unit	Test Method		
Melt Mass-Flow Rate (MFR)	13	g/10 min	ASTM D1238		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact (23°C)	75	J/m	ASTM D256		

Flammability	Nominal Value		Test Method
Flame Rating (3.18 mm, NC)	V-0		UL 94
Injection	Nominal Value	Unit	
Drying Temperature	71.1 - 82.2	°C	
Drying Time	2.0	hr	
Rear Temperature	200 - 220	°C	
Middle Temperature	205 - 225	°C	
Front Temperature	210 - 230	°C	
Nozzle Temperature	210 - 230	°C	
Processing (Melt) Temp	191 - 260	°C	
Mold Temperature	26.7 - 48.9	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

