

# Lusin® Clean 1061

Thermoplastic

Chem-Trend L.P.

## Message:

Ready-to-use Purging Compound for Screw, Barrel, Nozzle and Hot-runner of Thermoplastic Injection Moulding Machines

### Benefits

Especially developed for caps and closures made of polyolefin

Rapid cleaning effect

Suitable for hot-runner systems

Suitable as freezing mixture

According to FDA regulations (21 CFR) all components of the formulation of Lusin® Clean 1061 are either GRAS or permitted for direct or indirect food contact

The formulation of Lusin® Clean 1061 is in compliance with European Plastics Regulation No 10/2011

### Description

Lusin® Clean 1061 is a ready to use granular purging compound for screw, barrel, nozzle and hot-runner of injection moulding machines processing thermoplastic resins. The purging compound consists of high quality thermoplastic resins as well as highly efficient cleaning additives and does not contain abrasives. Lusin® Clean 1061 is especially recommended for color or material change as well as for the removal of black spots, carbon residues and cracked materials and can be used at processing temperatures up to 290°C (554°F). Lusin® Clean 1061 can also be used as freezing mixture for shutdown procedures during the weekend.

### Typical properties

Appearance : translucent yellow granules

Softening point : approx. 145°C

General Information	
Additive	Unspecified additive
Uses	Cleaning compound
Agency Ratings	FDA GRAS (Generally Recognized as Safe)
	FDA Food Exposure, Not Rated
	Europe No 10/2011
Appearance	Translucent
	Yellow
Forms	Particles

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT