

ADENE GHQAD

Polypropylene Homopolymer

A.D. Compound spa

Message:

ADENE GHQAD is a Polypropylene Homopolymer (PP Homopolymer) material filled with 40% talc. It is available in Europe or North America. Primary attribute of ADENE GHQAD: Homopolymer.
Typical application of ADENE GHQAD: Appliances

General Information			
Filler / Reinforcement	Talc,40% Filler by Weight		
Features	Detergent Resistant		
	Homopolymer		
Uses	Appliances		
Appearance	Grey		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	1.24	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	18	g/10 min	ISO 1133
Ash Content	40	%	ISO 3451-1
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	30.0	MPa	ISO 527-2
Tensile Strain			ISO 527-2
Yield	6.0	%	
Break	6.0	%	
Flexural Modulus	3800	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength (23°C)	2.5	kJ/m ²	ISO 180/1A
Unnotched Izod Impact Strength (23°C)	9.0	kJ/m ²	ISO 180/1U
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (1.8 MPa, Unannealed)	76.0	°C	ISO 75-2/A
Vicat Softening Temperature	99.0	°C	ISO 306/B

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

