

Sinpolene MBB2672

Low Density Polyethylene

Teknor Apex Asia Pacific PTE. LTD.

Message:

SINPOLENE MBB2672 is a polyethylene-based black masterbatch designed specifically for use in tubular film blowing, geomembranes, blow moulding, injection moulding, and sheet extrusion of polyolefins. SINPOLENE MBB2672 has very high pigment loading and thus offers high coloring value with superior quality and performance.

CHARACTERISTICS

- * Easy processing
- * Good dispersion
- * High jetness
- * Minimal wear effect on processing equipment

General Information			
Features	General		
Uses	Films		
	Sheet		
RoHS Compliance	RoHS compliance		
Forms	Particle		
Processing Method	Film extrusion		
	Sheet extrusion molding		

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.22	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/21.6 kg)	< 40	g/10 min	ASTM D1238
Carbon Black Content	50	%	ASTM D1603
Moisture Content		%	ASTM D3030

Additional Information
Recommended dosage: 2 - 5%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT