ENPRENE 655

Styrene Butadiene Styrene Block Copolymer En Chuan Chemical Industries Co,. Ltd.

Message:

ENPRENE 655 is a Styrene Butadiene Styrene Block Copolymer (SBS) product. It is available in Asia Pacific. Primary characteristic: linear polymer structure.

General Information			
Features	Linear Polymer Structure		
Appearance	Clear/Transparent		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.950	g/cm³	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/5.0 kg)	4.0	g/10 min	ASTM D1238
Oil Type (Unspecified Oil)	0.0	phr	
Ash Content	0.2	wt%	ASTM D1416
Styrene/Butadiene	Ratio: 40/60		ASTM D1416
Volatile Matter	0.30	wt%	ASTM D1416
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	88		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (300% Strain)	3.92	MPa	ASTM D412
Tensile Strength (Yield)	19.6	MPa	ASTM D412
Tensile Elongation (Break)	800	%	ASTM D412
Tear Strength	58.8	kN/m	ASTM D624

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

