PONACOM PS 5570-10

High Impact Polystyrene

Ponachem Compound GmbH

Message:

PONACOM PS 5570-10 is a high impact polystyrene product. It is available in Europe. The main characteristics are: impact resistance.

General Information			
Features	Impact resistance, high		
Appearance	Black		
Forms	Particles		
Physical	Nominal Value	Unit	Test Method
Density	1.05	g/cm³	ISO 1183
Melt Mass-Flow Rate (MFR) (200°C/5.0 kg)	8.0 - 12	g/10 min	ISO 1133
Water Absorption (Saturation, 23°C)	< 0.10	%	ISO 62
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength (23°C)	7.0 - 8.0	kJ/m²	ISO 179/1eA
Notched Izod Impact (23°C)	9.0	kJ/m²	ISO 180/1
Thermal	Nominal Value	Unit	
Melting Temperature	180 - 240	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

