

Okirol® E-6F

Expanded Polystyrene

DIOKI d.d.

Message:

Okirol® E-6F is expandable flame retardant polystyrene containing, apart from flame retardant agent, also pentane as the blowing agent. The product is supplied as spherical beads.

Okirol® E-6F is used for the manufacture of medium and high density blocks, panels with good mechanical properties intended for thermal insulation in construction industry, and industrial packaging.

Products made of Okirol® E-6F have fire characteristics in accordance with DIN 4102-1, class B1

General Information			
Additive	Blowing Agent		
	Flame Retardant		
Features	Flame Retardant		
Uses	Construction Applications		
	Insulation		
	Packaging		
	Reinforced Panels		
Agency Ratings	DIN 4102/B1		
	EC 1907/2006 (REACH)		
	EU 94/62/EC		
RoHS Compliance	RoHS Compliant		
Forms	Spheres		
Physical	Nominal Value	Unit	Test Method
Density			
-- ¹	0.0180	g/cm ³	
-- ²	0.0190 to 0.0300	g/cm ³	EN 1602
Apparent Density	0.62	g/cm ³	ISO 60
Flammability	Nominal Value		Test Method
Reaction to Fire	Class E		ISO 11925-2
Bead Size			ISO 2591-1
--	500.0 to 700.0	µm	
Range ³	400.0 to 800.0	µm	
Blowing Agent	5.0 to 6.5	%	ASTM 7132-05
NOTE			
1.	Minimum density of expanded beads		
2.	Density of molded product		
3.	>95%		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

