

EnviroPCABS 2090 HSL

Polycarbonate + ABS

West Michigan Compounding

Message:

EnviroPCABS 2090 HSL is a polycarbonate acrylonitrile butadiene styrene (PC ABS) product. It is available in North America. Typical application areas are: automotive industry. The main characteristics are: impact resistance.

General Information			
Features	Impact resistance, high		
Uses	Car interior parts		
	Automotive exterior parts		
Appearance	Black		
	Natural color		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.14	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR)	20	g/10 min	ISO 1133
Molding Shrinkage - Flow	0.70	%	ASTM D955
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress	52.0	MPa	ISO 527-2
Flexural Modulus	2200	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	580	J/m	ASTM D256
Dart Drop Impact	> 36.2	J	Internal method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT