

APEX® 2595-H

Flexible Polyvinyl Chloride

Teknor Apex Company

Message:

APEX® 2595-H is a Flexible Polyvinyl Chloride material. It is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America for extrusion.

Typical application of APEX® 2595-H: Hose/Tubing

General Information			
Uses	General Purpose		
	Hose		
	Profiles		
	Tubing		
Appearance	Natural Color		
	Opaque		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.35	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shore C	81		
Shore C, 15 sec	70		
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
Break	22.8	MPa	
100% Strain	16.0	MPa	
Tensile Elongation (Break)	340	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-22.0	°C	ASTM D746

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

