

ELASTOSIL® SOLAR 3210 A/B

Silicone

Wacker Chemie AG

Message:

Silicone Rubber, RTV-2

Photovoltaics, Renewable Energies

General Information			
Uses	Lenses		
	Optical Applications		
	Transparent Parts		
Uncured Properties	Nominal Value	Unit	Test Method
Color	Colorless		
Density	1.02	g/cm ³	ISO 2781
Viscosity	3.5	Pa · s	ISO 3219
Pot Life	100	min	
Cured Properties	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	45		ISO 868
Tensile Strength	7.00	MPa	ISO 37
Tensile Elongation at Break	100	%	ISO 37
Tear Strength	3.00	kN/m	ASTM D624B

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT