

Axpoly® r-PP51 1072

Polypropylene

Axion Polymers

Message:

Development Grade - r-PP51 1072

Axpoly® r-PP51 1072 is a high performance black polypropylene grade filled with 30% talc. The material offers improved rigidity and is designed for use in a variety of demanding end use applications.

Produced from 100% post-consumer raw materials, this product fits closely with our other Axpoly® recycled resin grades and offers the same set of user benefits, including:

Successfully replaces virgin resin

Huge savings in CO 2 impact

Appeals to 'greener' customers

Cost-down on raw material

Can help to reduce your carbon footprint

General Information		
Filler / Reinforcement	Talc,30% Filler by Weight	
Recycled Content	Yes	
Features	Medium Rigidity	
Agency Ratings	EC 1907/2006 (REACH)	
RoHS Compliance	RoHS Compliant	
Appearance	Black	
Forms	Pellets	
Physical	Nominal Value	Unit
Density	1.14	g/cm ³
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	7.0	g/10 min
Mechanical	Nominal Value	Unit
Tensile Stress	23.0	MPa
Tensile Strain (Break)	25	%
Impact	Nominal Value	Unit
Unnotched Izod Impact Strength	8.5	kJ/m ²

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT