

# IDI STC 2353 Woven

Thermoset Polyester

IDI Composites International

Message:

PRODUCT SERIES: STC 2300 SERIES SMC

PRODUCT DESCRIPTION: HIGH STRENGTH POLYESTER URETHANE HYBRID COMPOSITES

General Information			
Features	High Strength		
Forms	SMC - Sheet Molding Compound		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.70 to 1.90	g/cm <sup>3</sup>	ASTM D792
Molding Shrinkage - Flow	0.10	%	ASTM D955
Water Absorption (23°C, 24 hr)	0.10 to 0.30	%	ASTM D570
Hardness	Nominal Value	Unit	Test Method
Barcol Hardness	40 to 60		ASTM D2583
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	26200	MPa	ASTM D638
Tensile Strength	241	MPa	ASTM D638
Flexural Modulus	15200	MPa	ASTM D790
Flexural Strength	414	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	3200	J/m	ASTM D256

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

