

EPITEC® PC-910FH

Polycarbonate

Osterman & Company

Message:

EPITEC®PC-910FH is a polycarbonate (PC) material. This product is available in North America. EPITEC®The main characteristics of the PC-910FH are: flame retardant/rated flame.

General Information			
Appearance	Natural color		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.20	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (300°C/1.2 kg)	20	g/10 min	ASTM D1238
Molding Shrinkage - Flow	0.50 - 0.70	%	ASTM D955
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	112		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	2170	MPa	ASTM D638
Tensile Strength	60.7	MPa	ASTM D638
Flexural Modulus	2410	MPa	ASTM D790
Flexural Strength	93.1	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	690	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	129	°C	ASTM D648
RTI Imp	105	°C	UL 746
RTI	105	°C	UL 746
Flammability	Nominal Value		Test Method
Flame Rating (1.5 mm)	V-2		UL 94
Additional Information	Nominal Value		Test Method
Weatherability	f2		UL 746C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT