

# Dynaglide® DW 631

Polytetrafluoroethylene

DeWAL Industries

## Message:

These products are all polymeric PTFE compounds. Color - Gold, manufactured in thickness range of 0.010 To 0.064.

Used in both bearing and seal applications. Exhibits low friction and excellent wear properties. Can be used with soft surfaces such as aluminum and bronze.

General Information			
Features	Good Wear Resistance		
	Low Friction		
Uses	Bearings		
	Seals		
Appearance	Gold		
Physical	Nominal Value	Unit	
Thickness	0.381 to 1.63	mm	
Deformation	3.0	%	ASTM D621
Core ID	7.62	cm	
Width	12.7 to 305	mm	
Films	Nominal Value	Unit	Test Method
Tensile Strength - MD (Yield)	10.3	MPa	ASTM D882
Tensile Elongation - MD (Break)	180	%	ASTM D882

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT