

Hostacom TRC 352N E1

Polyolefin
LyondellBasell Industries

Message:

"Hostacom" TRC 352N is a 20% mineral filled, impact modified grade for interior applications with excellent impact/stiffness balance, good flowability properties and good scratch resistance. It has an outstanding blooming resistance at elevated temperatures and also low odour and low carbon emissions. The grade is available in color-matched, pellet form.

General Information	
Filler / Reinforcement	Mineral,20% Filler by Weight
Additive	Impact Modifier
Features	Good Flow
	High Impact Resistance
	High Stiffness
	Low Blooming
	Low to No Odor
	Scratch Resistant

Physical	Nominal Value	Unit	Test Method
Density	1.04	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	18	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield, 23°C)	21.6	MPa	ISO 527-2/50
Flexural Modulus ¹ (23°C)	2000	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength			ISO 179/1e
-30°C	3.0	kJ/m ²	
23°C	30	kJ/m ²	
Charpy Unnotched Impact Strength (23°C)	No Break		ISO 179/1eU
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (1.8 MPa, Unannealed)	54.0	°C	ISO 75-2/A
Vicat Softening Temperature	136	°C	ISO 306/A50

NOTE	
1.	2.0 mm/min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

