

Indothene CC

Low Density Polyethylene

Reliance Industries Limited

Message:

Indothene CC is a low density polyethylene product. It is available in Africa and the Middle East, Europe or Asia Pacific. The main characteristics are: carbon black.

General Information			
Additive	Carbon black (3%)		
Forms	Particles		
Physical	Nominal Value	Unit	Test Method
Density	0.933	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR)	0.25	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	9.80	MPa	ASTM D638
Tensile Elongation (Break)	450	%	ASTM D638
Electrical	Nominal Value		Test Method
Dielectric Constant (1 MHz)	2.35		ASTM D150
Additional Information			

Melt Flow Rate, ASTM D1238/O: 0.1 - 0.5 g/10 minESCR, ASTM D1603, 10% Igepal, 50°C: >48 hrs

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

