

# Hanwha Total PP BJ100

Polypropylene Impact Copolymer

HANWHA TOTAL PETROCHEMICALS Co., Ltd.

Message:

BJ100 is a block copolymer polypropylene resin for injection molding applications. This grade is designed to be processed in conventional injection molding equipment.

General Information			
UL YellowCard	E140331-222890		
Features	Block Copolymer		
	Rigidity, high		
	High molecular weight		
	Impact resistance, high		
	Good UV resistance		
	Good demoulding performance		
Uses	Lawn and Garden Equipment		
	Wheels		
	Electrical components		
	Tools/Parts Box		
	Household goods		
	Container		
	Outdoor application		
Forms	Particle		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Density	0.910	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	1.5	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	82		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	28.4	MPa	ASTM D638
Tensile Elongation (Break)	500	%	ASTM D638
Flexural Modulus	1270	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ASTM D256
-20°C	69	J/m	ASTM D256
0°C	98	J/m	ASTM D256
23°C	150	J/m	ASTM D256

Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	110	°C	ASTM D648
Optical	Nominal Value		Test Method
Gloss	75		ASTM D2457
Injection	Nominal Value	Unit	
Rear Temperature	70.0 - 200	°C	
Front Temperature	210 - 230	°C	
Mold Temperature	0.00 - 50.0	°C	
Injection Pressure	78.5 - 127	MPa	
Holding Pressure	58.8 - 98.1	MPa	
Injection instructions			
Cooling Time: 30 to 40 sec			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

