

Hyundai EP XLPE XC300/Natural

Crosslinked Polyethylene

HYUNDAI EP Co., Ltd.

Message:

Hyundai EP XLPE XC300/Natural is a Crosslinked Polyethylene product. It is available in Asia Pacific. Applications of Hyundai EP XLPE XC300/Natural include wire & cable, plumbing/piping/potable water and additive/masterbatch. Primary characteristic: crosslinkable.

General Information			
Features	Crosslinkable		
Uses	Cable Jacketing		
	Low Voltage Insulation		
	Masterbatch		
	Medium Voltage Insulation		
	Piping		
	Plumbing Parts		
	Wire & Cable Applications		
Appearance	Natural Color		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.952	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	7.0	g/10 min	ASTM D1238
Moisture Content	0.10	%	Internal Method
Black Spot ¹	0.00	count/g	Internal Method
NOTE			
1.	2.5 grams		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT