

DAI-EL™ LT-304

Fluoroelastomer

DAIKIN AMERICA, INC.

Message:

DAI-EL LT-304 is a fluoroelastomer which can be cured by peroxide whose cold temperature properties, a drawback of conventional fluoroelastomer, has been improved. It offers excellent mechanical properties, and bending and acid resistance, etc. The RT10 of this material is -30°C, providing excellent low-temperature sealing performance.

General Information	
Features	acid resistance
Appearance	Translucent
	Transparent-Slightly Yellow

Physical	Nominal Value	Unit	Test Method
Specific Gravity ¹	1.82	g/cm ³	JIS K6268
Mooney Viscosity (ML 1+10, 100°C)	50	MU	JIS K6300-1
Fluorine Content	65.0	wt%	

Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	65		

Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	3.00	MPa	JIS K6251
Tensile Strength	17.0	MPa	JIS K6251
Tensile Elongation (Break)	230	%	JIS K6251
Compression Set ² (200°C, 70 hr)	16	%	

NOTE	
1.	23°C
2.	25% compression

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT