

# Chemraz 615

Perfluoroelastomer

Greene, Tweed & Co.

## Message:

Chemraz 615 is a Perfluoroelastomer product. It is available in North America. Applications of Chemraz 615 include engineering/industrial parts, housings and sealing applications.

Characteristics include:

Chemical Resistant

Heat Resistant

General Information			
Features	Good Chemical Resistance High Heat Resistance Low Compression Set		
Uses	Housings Pump Parts Seals Valves/Valve Parts		
Appearance	Black		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	2.01	g/cm <sup>3</sup>	ASTM D297
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	80		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress			ASTM D1414
50% Strain	2.76	MPa	
100% Strain	6.89	MPa	
Tensile Strength (Break)	11.7	MPa	ASTM D1414
Tensile Elongation (Break)	170	%	ASTM D1414
Thermal	Nominal Value	Unit	
Service Temperature	-18 to 324	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

**Susheng Import & Export Trading Co.,Ltd.**

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

