

Baytec® MP-080

Polyurethane (Polyether, MDI)

Covestro - PUR

Message:

Baytec MP-080 diphenylmethane diisocyanate (MDI)-terminated polyether prepolymer is based on polypropylene ether glycol (PPG).

| General Information | | | |
|----------------------------|---------------|------|-------------|
| Forms | Liquid | | |
| Elastomers | Nominal Value | Unit | Test Method |
| Tensile Stress | | | ASTM D412 |
| 100% strain | 4.32 | MPa | ASTM D412 |
| 300% strain | 7.43 | MPa | ASTM D412 |
| Tensile Strength (Break) | 9.93 | MPa | ASTM D412 |
| Tensile Elongation (Break) | 470 | % | ASTM D412 |
| Additional Information | | | |

Appearance: Yellow viscous liquidNCO: 7.8 to 8.2 wt%Viscosity at 25°C: 2500 mPa-sSpecific Gravity at 25°C: 1.08Flash Point, PMCC: 200°CDensity at 25°C: 9.05 lb/gal

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

