Sumikon® PM-6930

Phenolic

SBHPP

Message:

General Information

SUMIKON® PM-6930 (Type H Black) is Glass fiber and Inorganic filler filled resol resin (non-anmonia phenolic) molding compound with good electronic property and heat resistance. This grade is official registered UL with V-0 (t=4.5).

General Information					
Filler / Reinforcement	Glass fiber reinforced material				
	Inorganic filler				
Features	Good electrical performance				
	Heat resistance, medium				
RoHS Compliance	RoHS compliance				
Appearance	Black				
Forms	Powder				
	Particles				
Processing Method	Resin transfer molding				
	Compression molding				
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.84	g/cm³	JIS K6911		
Molding Shrinkage - Flow	0.13	%	JIS K6911		
Water Absorption (Equilibrium)	0.070	%	JIS K6911		
Hardness	Nominal Value	Unit	Test Method		
Rockwell Hardness (M-Scale)	107		ASTM D785		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength	93.0	MPa	JIS K6911		
Flexural Modulus	14800	MPa	JIS K6911		
Flexural Strength	156	MPa	JIS K6911		
Compressive Strength	186	MPa	JIS K6911		
Impact	Nominal Value	Unit	Test Method		
Charpy Notched Impact Strength	4.4	kJ/m²	JIS K6911		
Thermal	Nominal Value	Unit	Test Method		
Deflection Temperature Under Load (1.8					
MPa, Unannealed)	300	°C	JIS K6911		
Electrical	Nominal Value	Unit	Test Method		
Dielectric Strength ¹	10	kV/mm	JIS K6911		
Insulation Resistance			JIS K6911		

2	2.0E+13	ohms	JIS K6911	
3	8.0E+12	ohms	JIS K6911	
Flammability	Nominal Value	Unit	Test Method	
Flame Rating (4.5 mm)	V-0		UL 94	
NOTE				
1.	Method B (step by step)			
2.	As molded			
3.	After boiling			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

