

ASI POLYPROPYLENE PP 3480-01

Polypropylene Impact Copolymer

A. Schulman Inc.

Message:

PP 3480 is a high flow, high impact copolymer polypropylene suitable for injection molding applications which require a material with the following properties.

General Information		
Features	High Flow	
	High Impact Resistance	
	Impact Copolymer	
Uses	Automotive Applications	
Processing Method	Injection Molding	
Physical	Nominal Value	Unit
Specific Gravity	0.898	g/cm ³
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	30	g/10 min
Hardness	Nominal Value	Unit
Rockwell Hardness (R-Scale)	71	
Mechanical	Nominal Value	Unit
Tensile Strength (Yield, 23°C)	21.0	MPa
Tensile Elongation (Yield, 23°C)	6.0	%
Flexural Modulus (23°C)	1000	MPa
Flexural Strength (23°C)	25.0	MPa
Impact	Nominal Value	Unit
Notched Izod Impact (23°C)	150	J/m
Unnotched Izod Impact ¹ (-30°C)	No Break	
Thermal	Nominal Value	Unit
Heat Deflection Temperature	98	°C
NOTE		
1.	500 J/m	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

