

LNP™ STAT-KON™ ZX05043 compound

Polyphenylene Ether + PS
SABIC Innovative Plastics Europe

Message:

LNP STAT-KON ZX05043 is a compound based on PPE+PS Blend resin containing Glass Fiber, PTFE, Carbon Fiber.
Also known as: LNP* STAT-KON* Compound ZCFL-4028
Product reorder name: ZX05043

General Information			
Filler / Reinforcement	Glass\Carbon Fiber		
Additive	PTFE Lubricant		
Features	Lubricated		
RoHS Compliance	RoHS Compliant		
Physical	Nominal Value	Unit	Test Method
Density	1.41	g/cm ³	ISO 1183
Molding Shrinkage - Flow ¹	0.50 to 1.5	%	Internal Method
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Break)	111	MPa	ISO 527-2/5
Tensile Strain (Break)	0.70	%	ISO 527-2/5
Flexural Modulus ²	12600	MPa	ISO 178
Flexural Stress	133	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength ³ (23°C)	5.0	kJ/m ²	ISO 180/1A
Unnotched Izod Impact Strength ⁴ (23°C)	15	kJ/m ²	ISO 180/1U
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature ⁵ (1.8 MPa, Unannealed, 64.0 mm Span)	130	°C	ISO 75-2/Af
Electrical	Nominal Value	Unit	Test Method
Surface Resistivity	1.0E+2 to 1.0E+3	ohms	ASTM D257
NOTE			
1.	Tensile Bar		
2.	2.0 mm/min		
3.	80*10*4		
4.	80*10*4		
5.	80*10*4 mm		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

