

Allen ABS AX7/LXS

Acrylonitrile Butadiene Styrene
SEKISUI Polymer Innovations, LLC

Message:

AX7/LXS is a general purpose ABS that has high impact strength.
Common Applications:
Covers and Housings
Vehicle Interiors
Vehicle Exteriors with Paint or korad
Instrument Cases
Features and Benefits:
Custom color matching
Good forming properties
Edge trim easily used in future orders
Korad can be applied for UV protection
High gloss finish

General Information			
Features	High Gloss		
	High Impact Resistance		
Uses	Automotive Applications		
	General Purpose		
	Housings		
	Protective Coverings		
Processing Method	Sheet Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.02 to 1.04	g/cm ³	ASTM D792
Molding Shrinkage - Flow	0.50 to 0.70	%	ASTM D955
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	34.5	MPa	ASTM D638
Flexural Modulus	2000	MPa	ASTM D790
Flexural Strength	55.8	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ASTM D256
-18°C	110	J/m	
23°C	320	J/m	
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	90.6	°C	ASTM D648
CLTE - Flow (-40 to 38°C)	1.0E-4	cm/cm/°C	ASTM E831
Flammability	Nominal Value		Test Method
Flame Rating (1.52 mm)	HB		UL 94

Optical	Nominal Value	Test Method
Gloss (60°)	80	ASTM D523

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

