

SECCO LL0220AA

Linear Low Density Polyethylene
Shanghai SECCO Petrochemical Co., Ltd

Message:

SECCO LL0220AA is a linear low density polyethylene material. This product is available in the Asia-Pacific region. The main characteristics of SECCO LL0220AA are: ROHS certification.
The typical application field of SECCO LL0220AA is: food contact application

General Information			
Agency Ratings	FDA 21 CFR 177.1520(c) 3.1a		
	FDA 21 CFR 177.1520(c) 3.2a		
RoHS Compliance	RoHS compliance		
Physical	Nominal Value	Unit	Test Method
Density	0.919	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	2.0	g/10 min	ISO 1133
Films	Nominal Value	Unit	Test Method
Tensile Stress			ISO 527-3
MD: Yield	10.0	MPa	ISO 527-3
TD: Yield	11.0	MPa	ISO 527-3
MD: Fracture	36.0	MPa	ISO 527-3
TD: Fracture	28.0	MPa	ISO 527-3
Tensile Elongation			ISO 527-3
MD: Fracture	1000	%	ISO 527-3
TD: Fracture	1200	%	ISO 527-3
Dart Drop Impact	110	g	ISO 7765-1
Elmendorf Tear Strength			ISO 6383-2
MD	1.5	N	ISO 6383-2
TD	3.7	N	ISO 6383-2

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT