

GERMAFORM 13 PTFE 18 SI 2-6940

Acetal (POM) Copolymer
Kunststoff-Kontor-Hamburg GmbH

Message:
GERMAFORM 13 PTFE 18 SI 2-6940 is an Acetal (POM) Copolymer material. It is available in Europe. Primary attribute of GERMAFORM 13 PTFE 18 SI 2-6940: Lubricated.

General Information			
Additive	PTFE Lubricant (18%)		
	Silicone Lubricant (2%)		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	1.43	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	10	g/10 min	ISO 1133
Water Absorption (Saturation, 23°C)	0.70	%	ISO 62
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	2200	MPa	ISO 527-2
Impact	Nominal Value	Unit	Test Method
Charpy Unnotched Impact Strength	60	kJ/m ²	ISO 179

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT